

CTB-10 W/V01

CONTROL UNIT



when communication is critical

FEATURES

- Waterproof operator panel with 10 lines selection,
- With external loudspeaker HP-8
- Option, microphone P-66 and P-66/10
- Operates with CU-10 or CU-100 central unit
- Single call/ / Group Call / All Call facility
- Dimmable panel background light
- Line buttons with memory light
- Buzzer indication of incoming calls
- Step volume control
- Call signal
- Wall mounting



SPECIFICATIONS

Material / finish	Aluminium / Stainless steel, Box ABS plastic
Mounting	Wall with 4 x 4mm screws
Terminals	Plugable screw terminals for cable max. 2,5mm ²
Dimension (mm)	300W x 160H x 156D
Weight	Approx. 1.4 kg
External connections	Central unit, ext. loudspeakers
Front panel	Graphic front film
Switches	Push button type with LED indication
Microphone contact	Amphenol w/cover IP-67
WP Microphone	P-66 or P-66/10, see separate datasheet
Loudspeaker	External loudspeaker, HP-8 8ohm.
Protection	IP-66

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3005020002	CTB-10W-V01 Control Unit WP 10 Lines Waterproof, INCL.HP-8	1.4 kg
Related Items		
3005020039	PT-66 Handmicrophone WP W/PTT 3M Cord W/4 PIN Plug IP-66	0.3 kg
3005020040	PT-66/10 Handmicrophone WP W/PTT 10M Cord,4 PIN Plug - IP-66	0.4 kg

CTB-10 W/V01 CONTROL UNIT

