

# ETB-5

CENTRAL PANEL MOUNTED



when communication is **critical**

## FEATURES

- Master station with 5 lines selection
- All Call facility
- Monitor-speaker / microphone
- Connector for gooseneck or handheld microphone
- Dimable memory light
- Line buttons with memory light
- Buzzer indication of incoming calls
- Step volume control
- Call signal
- Output for extra signal device all lines
- 24V DC power supply



## SPECIFICATIONS

Material / finish	Aluminium / black
Mounting	Flush with 4 x 4 mm screws
Terminals	Plugable screw terminals for cable max. 2.5 mm <sup>2</sup>
Cable gland	6 x PG-16
IP rating	IP-41
Dimension (mm)	240W x 144H x 130D (with glands)
Cut out dimension	224 x 132 mm
Weight	Approx. 1.6 kg
Microphone input	Contact for handheld and gooseneck -microphone
Switches	Push button type with LED indication
Power supply	24 - 32 VDC
Current consumption	0.9 A
Output power	15 W RMS
Frequency range	200 Hz - 8 KHz (-3 dB)
Temperature operating	-20 + 55°C

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3005020022	ETB-5 Central Panel Mounted 5 Lines, 24V DC, 2A	1.6 kg
Related items 3005020065	Wall Mounted Box for ETB-5/10 and CTB-10/20	0.4 kg

ETB-5 CENTRAL PANEL MOUNTED

