

3006200005

RELAY BOX 24V DC

 IP66



DESCRIPTION

- Separate relay timer unit for operation of 24V DC visible and/or audible signal units
- Built-in timer circuit - signaling time of 20 seconds as standard
- Alarm stop button
- Wall mounting
- Suitable for installation in noisy areas

SPECIFICATIONS

GENERAL

Connections	Screw terminals
Material	Flame retardant blend plastic housing
IP rating	IP- 66
Dimensions	224W x 80H x 63D mm
Weight	0.60 kg

Created: 04.03.2015, updated: 18.12.2015

page 1/2

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Vingtort-Stentofon products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend. Zenitel - All rights reserved.

TECHNICAL DIMENSIONS

