

2330040025

VSP-512-AKHS-10

Headset with headband ATEX certified incl. 10m cable



DESCRIPTION

- Rugged headset for VSP EX application
- Noise-cancelling microphone
- High quality audio
- Optional in-ear monitors may be connected for added damping in extreme environments
- Standard 4-pole Nexus connector for easy connection/replacement
- Includes 2330040027 AK6797(10mtr) "EX approved Cable for headset with PTT"
- Designed for VSP EX explosion-proof station VSP-512

SPECIFICATIONS

GENERAL

Weight	0,4 kg
Operational Temperature	-40°C to +60°C
Ingress Protection	IP-66
Impedance	230 ohm
Sensitivity (mic)	4 mV / 220 ohm
Frequency Response	90-7000 Hz
Noise Reduction	-12dB @ 1kHz
SOUND ATTENUATION	
Above 1kHz:	-35 to -40 dB
500-1000 Hz	-27.5 to -35 dB
125-500 Hz	-15 to -27.5 dB
H84	31 dB (with in-ear monitor: 39 dB)
M84	26 dB (with in-ear monitor: 37 dB)
L84	20 dB (with in-ear monitor: 33 dB)
SNR84	29 dB (with in-ear monitor: 40 dB)
NRR	21 dB

TECHNICAL DIMENSIONS

