HEAVY DUTY TELEPHONE

ANALOGUE WITH DOOR



when**communication**is**critical**

FEATURES

- Made for marine environment
- Full phone keypad plus special function keys
- Door has smart stay-open or stay-shut mechanism
- Good audio quality
- · Fluorescing buttons enhance correct dialing
- Magnetic reed hook-switch gives minimal tear and wear
- Powered by phone line



DESCRIPTION

The VINGTOR Heavy Duty Analogue Telephone is made for environments that need a telephone which withstand rough usage and treatment. The telephone is well suited for indoor marine usage – due to the thick aluminum casing, the stainless steel materials, the steel cable into the phone from bottom, and the fluorescing keypad. Industrial indoor environments are also suitable. The telephone is easy to use with a full keyboard with large buttons. Function keys are for :

- Redial (redials last number)
- Store (storing speed dial numbers)
- Pick (pushed before a key when using speed dial)

External ringer unit recommended – like the HB-90, HB-105 or CRB-7.

Wall mounting plate in stainless steel is suitable for installations which do not give rear access to the phone.

SPECIFICATIONS

Dimensions (WxHxD)	205 x 320 x 148	
Weight	5,0 kg	
Mounting	Wall mounted. Optional Wall Mounting Plate for non-rear access	
Temperature range	-30°C - 60°C (ambient)	
Humidity range	10% – 95% (relative)	
Power	48 – 69 VDC	
Ringing intensity	> 70 dB	
Construction	5 mm aluminum casing and stainless steel components	
Phone cable	Stainless steeL 60 cm, from below phone	
Handset	Strong, anti-knock resistance	
Handset cable	40 cm crimp cable	
IP class	IP 67	
Standard buttons	12 buttons : 1-9, 0, *, #	
Function buttons	STORE: used to store up to 10 speed- dial numbers (max 16 digits) PICK: pushed before standard button to initiate speed dialing REDIAL: dial once more the last dialed number	

VINGTOR | DATASHEET 2213000200

www.vingtor.com

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
2213000200	Heavy Duty Analogue Telephone Door	5 0 Va
2213000200	Wall mounting plate (Included)	5,0 Kg 0.2 Ka
Supplementary equipment		
JB-15T	Junction box	0.1 Kg
CRB-7	Relay box 24VDC, 110/220VAC - signal unit WP	
HB-90	Telephone tone caller indoor 60-100V AC, 90dB	0.2 Kg
HB-105	Telephone tone caller indoor 60-100V AC, 105dB	

HEAVY DUTY ANALOGUE TELEPHONE DOOR

