

SPA-M1H-V2

PA PANEL SINGLE



when communication is critical

FEATURES

- PA Panel for single system, all call
- Delivered with handheld microphone
- Built-in pre-amplifier with preset signal level and tone controls
- TALK button on panel and handheld microphone
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker (From hardware version 4.0)

DESCRIPTION

This panel gives All Call Message in a SPA-V2 public address and general alarm single system. Installation in consoles or wall indoor.

Local mute function is used to break audio to loudspeakers where proximity to pa panel cause feedback. Available from hardware version 4.0 This function must be in combination with relay box.

SPECIFICATIONS

Size (WxHxD)	144 x 144 x 82
Weight w/microphone	0.5 kg
Material	Black anodized aluminium
Mounting	Flush, wall with use of back box
Output signal	0.775mV 0dB
Sensitivity microphone	-55dB +- 3dB at 1kHz rel. 1V/Pa
Connections	Plugable screw terminals for 2.5 mm ² cable
Cable glands	4 x PG-16
Cable size	6 x 2 x 0.75mm ²
Local mute relay, output	24V DC @ maximum 50 mA
IP-rating	IP-44



ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3005010146	SPA-M1H-V2 PA PANEL SINGLE FOR ALL CALL- FLUSH-W/HANDHELD MIC ETC-1	0.5 kg
3005010155	SPA-M6B0KS Back Box For Wall Mounting	0.3 kg

SPA-M1H-V2 PA PANEL SINGLE

