

SPA-M1S-D

PA PANEL DUAL



when communication is **critical**

FEATURES

- PA Panel for dual system , all call
- Delivered with gooseneck microphone
- Built-in pre-amplifier with preset signal level and tone controls
- TALK button on panel for All Call message
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker (From hardware version 4.0)

DESCRIPTION

This panel gives All Call Message in a SPA-V2 public address and general alarm dual system. Installation in consoles or wall indoor.

Local mute function is used to break audio to loudspeakers where proximity to pa panel cause feedback. Available from hardware version 4.0 This function must be in combination with relay box.



SPECIFICATIONS

Size (WxHxD)	144 x 144 x 82
Weight w/microphone	0.5 kg
Material	Black anodized aluminium
Mounting	Flush, wall with use of back box
Output signal	0.775mV 0dB
Sensitivity microphone	2K / 4mV
Connections	Plugable screw terminals for 2.5 mm ² cable
Cable glands	4 x PG-16
Cable size	6 x 2 x 0.75mm ²
Protection	IP-44
Local mute relay, output	24V DC @ maximum 50 mA

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3005010148	SPA-M1S-D PA Panel dual for all call - flush - w/gooseneck microphone MB-30G	0.5 kg
3005010155	SPA-M6BOKS Back Box For Wall Mounting	0.3 kg

SPA-M1S-D PA PANEL DUAL

