

SPA-M6H-V2

PA PANEL SINGLE W/6 ZONES, ALL CALL AND DIMMER-FLUSH-W/HANDH



when communication is critical

FEATURES

- PA-panel for single system
- Delivered with handheld microphone
- Built-in pre-amplifier with preset signal level and tone controls
- 6 zone selection buttons
- ALL, TALK and dimmer buttons.
- Microphone with PTT
- Replaceable text label to each zone button
- Zone buttons have activation confirmation light
- Flush mounting, back box for wall mounting is available
- Zone memory for last zone selection on (2340110001 SPA-M6HM-V2)
- Local mute contact for external loudspeaker (From hardware version 4.0)



DESCRIPTION

This panel gives messages in one to six zones in a SPA-V2 public address and general alarm single system. Installation in consoles or on-wall indoor.

Version 2340110001 SPA-M6HM-V2 have zone memory for the previous zone selection when talk button is released.

Function Local mute is used for instances where feedback is caused by close proximity between a PA panel and a loudspeaker. From hardware version 4.0. This function must be in combination with relay box.

SPECIFICATIONS

Size (WxHxD)	144 x 144 x 82
Weight w/microphone	0.5 kg
Material	Black anodized aluminium
Mounting	Flush, wall with use of back box
Output signal	0.775mV 0dB
Sensitivity microphone	-55dB +- 3dB at 1kHz rel. 1V/Pa
Connections	Plugable screw terminals for 2.5 mm ² cable
Cable glands	4 x PG-16
Cable size	6 x 2 x 0.75 mm ²
Local mute relay, output	24V DC @ maximum 50mA

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3005010158	SPA-M6H-V2 PA Panel Single w/6 Zones, All Call and Dimmer-Flush-w/Handh	0.5 kg
2340110001	SPA-M6HM-V2 PA Panel Single W/6 Zones W/Memory and Handheld Mic	0.5 kg
3005010155	SPA-M6BOKS Back Box For Wall Mounting	0.3 kg
1020600992	IRR-3 Relaybox 24V DC or 220V AC signal unit waterproof	0.35 kg

SPA-M6H-V2PA PANEL SINGLE W/6 ZONES, ALL CALL AND DIMMER-FLUSH-W/HANDH

