

SPA-M6S-V2

PA PANEL SINGLE W/6 ZONES, ALL CALL AND DIMMER-FLUSH-W/GOOSE



when communication is **critical**

FEATURES

- PA-panel for single system
- Delivered with gooseneck microphone
- Built-in pre-amplifier with preset signal level and tone controls
- 6 zone selection buttons
- ALL, TALK and dimmer buttons. Talk button on panel
- Replaceable text label to each zone button
- Zone buttons have activation confirmation light
- Flush mounting, back box for wall mounting is available
- Zone memory for last zone selection on (2340110002 SPA-M6SM-V2)
- Local mute contact for external loudspeaker (From hardware version 4.0)



DESCRIPTION

This panel gives messages in one to six zones in a SPA-V2 public address and general alarm single system. Installation in consoles or on-wall indoor.

Version 2340110002 SPA-M6SM-V2 have zone memory for the previous zone selection when talk button is released.

Local mute function is used to break audio to loudspeakers where proximity to pa panel cause feedback. Available from hardware version 4.0. This function must be in combination with relay box.

SPECIFICATIONS

Size (WxHxD)	144 x 144 x 82
Weight w/microphone	0.6 kg
Material	Black anodized aluminium
Mounting	Flush, wall with use of back box
Output signal	0.775mV 0dB
Sensitivity microphone	2K / 4mV
Connections	Plugable screw terminals for 2.5 mm ² cable
Cable glands	4 x PG-16
Cable size	6 x 2 x 0.75 mm ²
Local mute relay, output	24V DC @ maximum 50mA

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3005010161	SPA-M6S-V2 PA Panel Single w/6 Zones, All Call and Dimmer-Flush-w/Goose	0.6 kg
2340110002	SPA-M6SM-V2 PA Panel Single w/6 Zones, with memory and gooseneck mic.	0.6 kg
3005010155	SPA-M6BOKS for SPA-M1 & M6 Panels when Wall Mounted	0.3 kg
1020600992	IRR-3 Relaybox 24V DC or 220V AC signal unit waterproof	0.35 kg

SPA-M6S-V2 PA PANEL SINGLE W/6 ZONES, ALL CALL AND DIMMER-FLUSH-W/GOOSE

