

CL-200T

CEILING LOUDSPEAKER STEEL FIREDOME



when communication is **critical**

FEATURES

- Made for marine environment
- Good audio quality
- Steel back box to reduce fire risk and spread
- Spring fasteners and screw holes for vibrating environments
- Spring fasteners only for non-vibrating environments
- Adjustable power tapping to accommodate separate room sizes
- Back box glands increase stability of wire connectivity
- Supports loop wiring with 2 x 20 mm back box glands
- Includes thermal fuse, transformer and supports 100V lines



DESCRIPTION

The VINGTOR flush mounted ceiling speaker is made for the most demanding environments – withstanding dusty, salty and vibrating environments. The speaker is well suited for marine usage – by use of zinc-treated steel grille with painted front and fully painted back box.

The speaker is easy to install due to the one-hand adjustable power tapping button. The back box glands enhance the speaker and provide extra coverage against dust, humidity and water. Using both glands facilitates loop-wiring and reduces the need for costly junction boxes



SPECIFICATIONS

Material	Painted front of zinc plated steel grille, painted steel back box
Colour	RAL9010
Dimension (mm)	199 x 121,5
Mounting	Flush mounted – ceiling or wall Clamps and/or 3 screws (4 mm holes)
Termination	Screws (plus (+), minus (0) and ground (optional)
Glands	2 x M20 (Cable diameter 6 - 14mm)
Weight	1,45 kg
Temperature range	-20°C – 90°C (ambient)
Rated / Max power	6W / 9W
Protection	IP-44
Power tapings	1-2-4-6W
SPL 1W / 1m	92 dB
Fuse	Thermal type 2.5 A at 125V AC
Effective frequency range	150 – 20000 Hz

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
2131000100	CL-200T Ceiling loudspeaker, steel fire dome	1,45 Kg

CL-200T CEILING LOUDSPEAKER STEEL FIREDOME

