

3006204193

Alarm Interface Module

Alarm interface module with software for IPTV



DESCRIPTION

The Alarm Interface Module is used to provide a mute (or turn-off) TV option and to send a dynamic message to the screen during PA/GA.

- 35mm DIN rail or direct surface mount
- 10/100 RJ45 Ethernet port
- 12x Terminals for connecting Alarm contacts, e.g.:
 - General alarm
 - Abandon
 - Manual
 - Fire Crew
 - Fire ALL
 - Other alarm
- When input contact is closed, every alarm input sends different UDP command to network server
 - For example: "ALARM 1 ON", "ALARM 1 OFF", etc.
- Commands can be sent every 2ms (to have enough time for network to react)
- Customizable UDP commands up to 38 Characters, e.g. command could be "/ par1 / par2 - ALARM01 STATUS ACTIVE"
- Commands can be sent constantly during closed contact to have fail-safe function
- Priorities between alarms (1st General, 2nd Abandon, etc.)
- Web interface with all information
 - Unit IP address, subnet mask, default gateway, Local (UDP) port
 - Remote IP address, Remote (UDP) port
 - On/Off commands for each alarm
- Fully web customizable
 - Change unit IP address
 - Change unit subnet mask
 - Change default gateway
 - Change unit local (receiving) port
 - Set remote IP address
 - Set remote (destination) port
 - Customize each alarm command (every alarm ON and OFF commands)

SPECIFICATIONS

PHYSICAL AND POWER

Mounting	35mm DIN rail or wall/desk mounting
Weight	0,2 Kg
Dimension (W x H x D)	88 x 90 x 58 mm
IP / NEMA Rating	IP-20
Power supply	+24VDC (18-36VDC), Power reverse polarity protection
Max. Current consumption	70mA @24VDC (1,68 Watt)

ENVIRONMENT

Operating Temperature	-0°C to +40°C
Storage Temperature	-40 to 85°C
Humidity (no condensing)	95% RH

INPUTS / OUTPUTS

10/100 RJ45 Ethernet port
Power input 18-36 VDC
6x input contacts (normal open contacts)
1x relay contact

USED WITH

2320005018
IPTV SERVER 8000 V2



2320005019

IPTV SERVER 8000 V2 W/ 8TB

IPTV Server 8000 with configuration, 8TB, 8x DVB-S/S2/T/T2/C+8x CI slots, V2

