

6200R Basic Unit

Art. No. 4000019765 and 4000100304



DESCRIPTION:

The P-6200R basic unit is a digital communication system covering all aspects of internal and external communication, information exchange on-board marine vessels, offshore installations, and to/from onshore operation centers.

FEATURES:

- Up to 24 analog or digital lines per unit
- 48 VoIP registrations per unit
- 2 x 100 Mbit Ethernet ports
- Modular terminal interface design
- PBX features such as group calls, paging groups, alert groups, conferences, switchboard, direct inward dialing
- VoIP or FXO trunk lines
- SIP/RTP protocol support
- Dual redundant power supply



ELECTRICAL SPECIFICATIONS:

Power supply	PN 19765: (AC/DC) - 220/110VAC, 48/24VDC (dual redundant) PN 100304: (AC/AC) - 220/110VAC, 220/110VAC (dual redundant)
Power consumption	12W (idle), 65W (max)
Heat dissipation	35W (max)
Compass safe distance	0.2 m

ENVIRONMENTAL SPECIFICATIONS:

Temperature	-15°C to +55°C
Humidity	93% @ +40°C
Protection	IP-20

Technical Data Sheet

6200R Basic Unit

Art. No. 4000019765 and 4000100304

PHONTECH
by ZENITEL GROUP

MECHANICAL SPECIFICATIONS:

Dimension (WxHxD)	19" 1U rack mounted, D = 293 mm
Weight	3.5 kg
Material	Steel / aluminum / plastic
Color	RAL 9005
Mounting	Rack / console
Fixing	4 pcs M5 bolts
Access	Front
Cable entry	Rear
Connector type	RJ45 / Dsub 25p
Manufacturer	Zenitel

CERTIFICATES / COMPLIANCES:

IEC 60945 Marine equipment

The unit has DNV-GL, ABS and RMRS (RS) type approvals and are also compatible with NORSOK.


RELATED PRODUCTS:

Phontech P-6202 Billing Unit. Supplementary unit to provide call record logging and billing.

6200R Basic Unit

Art. No. 400019765 and 4000100304

DIMENSIONS / LAYOUT (PN 19765 – AC/DC)



6200R Basic Unit

Art. No. 400019765 and 4000100304

DIMENSION / LAYOUT (PN 100304 – AC/AC)

