

4000016789

P-3131

Remote Master Station



DESCRIPTION

- 15 substation/loudspeaker lines, master station and 3 other remote control units
- Control output for external call signal device
- Integrated microphone
- Connection for handheld microphone
- Connection for additional, external loudspeaker
- Volume control in front
- 12 W output power
- Complies with IEC 60945 Standard for Marine Equipment
- RMRS type approval and compatible with NORSOK

The CIS Remote Master Station P-3131 is a watertight talk-back operator panel for the Command Intercom System. Through the Master Station P-3130 it can remotely talk to all substations, type P-9xxx. It can also communicate directly with the Master Station 3130 and Remote Master Stations type P-3132. The P-3131 requires an external loudspeaker to operate.

The functionality comprises point-to-point, group and all calls as well as emergency Public Address.

SPECIFICATIONS

MECHANICAL

Dimensions (WxHxD)	200x150x78 mm
Weight	0.75 kg
Color	RAL 7035/9005
Material	Polycarbonate
Mounting	Bulkhead
Fixing	4 x M4 bolts
Access	Front
Cable Entry	Bottom
Gland Type	1x PG 21 / 1x PG 13.5

ELECTRICAL

Power Supply	24 VDC (22-32 VDC)
Frequency Range	300-3400 Hz
Power Consumption	25W (peak), 3W (typical)
Fuse	5x20 mm, 2A T
Heat Dissipation (typical/max)	< 3W / 10W
Termination	Screw terminals ≤ 1.5 mm ²
Compass Safe Distance	> 5 m

ENVIRONMENTAL

Temperature	-15°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-55

TECHNICAL DIMENSIONS

