

4000017150

P-5123

Telephone with Relay



DESCRIPTION

- DTMF analog telephone
- Loudspeaking / handset operation
- Memory buttons
- Built-in relay, max 5A
- External loudspeaker connection
- Complies with IEC 60945 Standard for Marine Equipment
- DNV GL type approval and compatible with NORSOK

The P-5123 is an analog flush-mounted console telephone with speakerphone functionality and illumination with dimmer.

SPECIFICATIONS

MECHANICAL

Dimensions (WxHxD)	192x240x121.5 mm
Weight	1.2 kg
Material	Aluminium / PC
Color	RAL 9005
Mounting	Flush / Console
Fixing	4 x M4 bolts
Access	Front
Cable Entry	Rear

ELECTRICAL

Power Supply	22-32 VDC / 10 W (max when external loudspeaker is connected)
Telephone line feed voltage	24-64 VDC
24-64 VDC Ring Voltage / Frequency	45 < R < 110V / 18 < F < 25 Hz
Termination	Screw terminals $\leq 1.5 \text{ mm}^2$
Compass Safe Distance	>1.9 m
Dial Method	DTMF (ITU-T Q23)
Ringing Volume	$\geq 75 \text{ dB(A)}$ at 1 m distance

ENVIRONMENTAL

Temperature	-15°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-22

TECHNICAL DIMENSIONS

