

4000087624 / 4000082999

P-7200

AC/DC & AC/AC LAN Switch



DESCRIPTION

- 24 Ethernet ports
- 2 SFP Gb ports
- Dual redundant power supply
- 10/100/1000 Mbps (24P)
- PoE (24 ports)
- 19" rack mounting
- Complies with IEC 60945 Standard for Marine Equipment
- DNV GL type approval and compatible with NORSOK

The P-7200 AC/DC or AC/AC LAN switch includes 24 Gb Ethernet and 2Gb SFP ports for fiber connectivity with 26 ports in total. The switch is fully manageable through the web and command line interface.

SPECIFICATIONS

MECHANICAL

Dimensions	19", 1U rack mounted, D=272 mm
Weight	3.9 kg
Color	RAL 9005
Material	Steel / Plastic
Mounting	Rack/ Console
Fixing	4 x M5 bolts
Access	Front
Cable Entry	Rear and Front

[Export Table Data](#)

ELECTRICAL

Power Supply	AC/DC: 90-250 VAC / 20-36 VDC. AC/AC: 90-250 VAC / 90-250 VAC
Output voltage	48VDC (PoE feed)
Power Consumption	225 W (max)
System power consumption	30 W
Heat Dissipation	45 W (max)
PoE power budget	150 W
Compass Safe Distance	<1.7 m

[Export Table Data](#)

ENVIRONMENTAL

Temperature	-15°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-20

[Export Table Data](#)

PORTS

RJ45 Ethernet	10/100/1000:24
SFP	Gigabit2
PoE ports	24

[Export Table Data](#)

SYSTEM STATUS

Power supply status LED	Primary/Secondary
System status LED	HW/SW status
Per-port LEDs	10/100/1000: PoE, link/activity

[Export Table Data](#)

TECHNICAL DIMENSIONS

